ILSS Industrial LED Saving System

Green05 STD IP22 & IK05

Green05 STD - jest standardową wersją świetlówki LED z obracanym trzonkiem T8, o szczelności IP22. Świetlówka na całej długości posiada aluminiowy radiator oddający ciepło z diody.
Możliwość wykonania świetlówki w kloszu mlecznym pryzmatycznym oraz przezroczystym pryzmatycznym dzięki czemu zwiększamy ilość światła na wyjściu.
Świetlówka została wyposażona w efektywną diodę dającą 130 Lm/W.

ZASTOSOWANIE
Garaże
Biura
Warsztaty
Korytarze
Sklepy
Małe magazyny

Temperature Characteristics T-ambient 25°C

Input Voltage:

Operating -30 +40 ℃
Storage -40 / +85 ℃

Electrical Characteristics

Input Voltage:

EU:AC100~240 50/60Hz
PF:⩾0.93 THD<20%
Power Efficiency:⩾0.87

Installation

1. Installation For Magnetic Ballast



ATTENTION: just replace starter with fuse for retrofit
only suitable for battens with magnetic ballast,not electronic ballast

2. Installation For Electronic Ballast



ATTENTION: Electronic ballast must be by-passed by a registered electrician

Light Distributon Curve



Dimension



L1(Nom)	L2(Nom)	L3(Nom)	L4(Nom)	D(Nom)	Cap-Base
588mm	894mm	1198mm	1498mm	26mm	G13

Model NO.	Power (W)	Light Source	LED QTY (pcs)	CCT (K)	Frosted Cover Lumens	Frosted Cover Lm/W	Clear Cover Lumens	Clear Cover Lm/W	CRI(Ra)	Beam Angle	Recommended Installation Height (m)
Green05 STD 600mm	11	3528	108	4000K	1320	120	1430	130	>80	120°	2 - 4
Green05 STD 900mm	17	3528	168	4000K	2040	120	2210	130	>80	120°	2 - 4
Green05 STD 1200mm	20	3528	216	4000K	2400	120	2600	130	>80	120°	3 - 6
Green05 STD 1500mm	24	3528	240	4000K	2880	120	3120	130	>80	120°	3 - 6
Green05 STD 1500mm	30	3528	336	4000K	3600	120	3900	130	>80	120°	4 - 8

CCT Range WW(3000K) NW(4000K) DW(5000K) CW(6500K)
Waterproof : IP22 & IK05